

	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△							△				
△							△				

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-30°C TO 75°C	STORAGE TEMPERATURE RANGE	-40°C TO 85°C
	VOLTAGE	5V AC	OPERATING HUMIDITY RANGE	-% TO -%
	CURRENT	1A	APPLICABLE CABLE	-

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
------	-------------	--------------	----	----

CONSTRUCTION

GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	<input type="checkbox"/>	<input type="checkbox"/>
MARKING	CONFIRMED VISUALLY.		<input type="checkbox"/>	<input type="checkbox"/>

ELECTRIC CHARACTERISTICS

CONTACT RESISTANCE	100 mA (DC OR 1000 Hz).		<input type="checkbox"/>	<input type="checkbox"/>
CONTACT RESISTANCE MILLIVOLT LEVEL METHOD.	20 mV MAX, 100 mA(DC OR 1000 Hz).	50 mΩ MAX.	<input type="checkbox"/>	<input type="checkbox"/>
INSULATION RESISTANCE	100 V DC	100 MΩ MIN.	<input type="checkbox"/>	<input type="checkbox"/>
VOLTAGE PROOF	100 V AC FOR 1min.	NO FLASHOVER OR BREAKDOWN	<input type="checkbox"/>	<input type="checkbox"/>
CAPASITANCE	MEASURE ADJACENT TWO CONTACTS AT 1000±10Hz AC VOLTAGE.	2 pF MAX	<input type="checkbox"/>	<input type="checkbox"/>

MECHANICAL CHARACTERISTICS

INSERTION AND WITHDRAWAL FORCES	MEASURED BY APPLICABLE CONNECTOR.	INSERTION FORCE 35 N MAX. EXTRACTION FORCE 7 N MIN.	<input type="checkbox"/>	<input type="checkbox"/>
MECHANICAL OPERATION	5000 TIMES INSERTIONS AND EXTRACTIONS.	① CONTACT RESISTANCE: 70 mΩ MAX. ② EXTRACTION FORCE 3 N MIN. ③ NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.	<input type="checkbox"/>	<input type="checkbox"/>
VIBRATION	FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm AT 2 h, FOR 3 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.	<input type="checkbox"/>	<input type="checkbox"/>
RANDOM VIBRATION	FREQUENCY 50 TO 2000 Hz, AT 15 min, FOR 3 DIRECTIONS.		<input type="checkbox"/>	<input type="checkbox"/>
SHOCK	490 m/s ² DIRECTIONS OF PULSE 11 ms AT 3TIMES FOR 6 DIRECTION. HALF SINE WAVE.		<input type="checkbox"/>	<input type="checkbox"/>

ENVIRONMENTAL CHARACTERISTICS

THERMAL SHOCK	TEMPERATURE -55 → 20~35 → 85 → 20~35 °C TIME 30 → 2~3 → 30 → 2~3 min UNDER 10 CYCLES,	① CONTACT RESISTANCE: 70 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.	<input type="checkbox"/>	<input type="checkbox"/>
HUMIDITY LIFE	TEMPERATURE -10~65 °C, HUMIDITY 90 TO 98 %, UNDER 7 CYCLES (168 h)	① INSULATION RESISTANCE: 10 MΩ MIN.(AT DRY) ② NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.	<input type="checkbox"/>	<input type="checkbox"/>
CORROSION SALT MIST	EXPOSED IN 5% SALT WATER SPRAY FOR 48 h. (JIS C 5402)	① CONTACT RESISTANCE: 70 mΩ MAX. NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.	<input type="checkbox"/>	<input type="checkbox"/>
SOLDERABILITY	SOLDERED AT TEMP.245°C FOR IN IMMERSION,DURATION,2~3 S.	SOLDER SHALL COVER A MINIMUM OF 95% OF THE SURFACE BEING IMMersed.	<input type="checkbox"/>	<input type="checkbox"/>

REMARKS	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
		<i>H. Tanaka</i>	<i>H. Tanaka</i>	<i>M. Nakamura</i>	<i>[Signature]</i>
Unless otherwise specified, refer to USB2.0 EIA364.					
Note QT:Qualification Test AT:Assurance Test ○:Applicable Test					

HS HIROSE ELECTRIC CO., LTD.		SPECIFICATION SHEET		PART NO.	
CODE NO.(OLD)		DRAWING NO.		UX60RA-MB-5ST	
		ELC4-124218		CL240-0007-5	
				1/1	

TO
Q1

