


| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A   | 24.1              |
| B   | 5/8-24NEF-2B      |
| C   | 8.6               |
| D   | 18.5              |
| E   | 53                |

| NO. | BESCHREIBUNG / DESCRIPTION              |
|-----|---|
| 2   | ISOLIERKÖRPER BUCHSE / INSULATOR SOCKET |
| 3   | DICKTKÖRPER / GROMMET                   |
| 6   | KONTAKTBUCHSE / CONTACT SOCKET          |
| 7   | ZYLINDERGHÄUSE / BARREL                 |
| 9   | ÜBERWURFMUTTER / COUPLING NUT           |
| 10  | DICHTRING FRONT / FRONT SEALING RING    |
| 16  | ENDGEHÄUSE GESCHIRMT / ENDBELL SHIELDED |



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.  
 Specification and Dimensions subject to change  
 Drawings illustrate normal insulator positioning

|                                |  |
|--------------------------------|--|
| <b>Material Specification:</b> |  |
| Shell Material:                | Aluminium alloy                                  |
| Shell Plating:                 | Olive drab chromate coating over cadmium plating |
| Insulator Material:            | Neoprene   |
| Contact Material:              | Copper alloy                                     |
| Contact Plating:               | Hard silver                                      |

all dimensions are in mm  
 Dimensions without tolerance indications are general tolerances in acc. with DIN7168m  
 drawing for CUSTOMER



description CA3106E10SL-4S-14  
 Plug, straight shielded  
 Endbell with clamp and bushing  
 Metric Crimp / Socket / Layout: 10SL-4

© All rights reserved. Reproduction or issue to third in any form whatever is only permitted with written authorization of ITT Cannon  
 page 1/1  
 revision 769 16. Jul 18