

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.






LOC FT	DIST 0	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
	A2	REVISED PER ECO-10-009375	05MAY10	HMR	CR

MATERIALS:
 HOUSING: POLYAMIDE 66, UL94V-0, GREEN.
 SOLDER PIN: BRASS, TIN PLATED.
 KEYS: POLYAMIDE 66, UL94V-0.

ELECTRICAL:
 CURRENT RATING: 12A, 300V.
 INSULATION WITHSTANDS: 2000VAC MIN.
 INSULATION RESISTANCE: 2000Mohm, 500VDC

OPERATING TEMP.: -40°C TO +105°C.

- 1 NON CUMULATIVE.
- 2 TE LOGO LOCATED IN APPROXIMATE AREA SHOWN.



THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm	TOLERANCES UNLESS OTHERWISE SPECIFIED:
	0 PLC ± -
	1 PLC ± 0.3
	2 PLC ± 0.25
	3 PLC ± -
	4 PLC ± -
	ANGLES ± -
MATERIAL	FINISH
-	-

DWN	S SCHLEGEL	05DEC2005
CHK	C RICHARD	12/5/05
APVD	C RICHARD	12/5/05
PRODUCT SPEC	-	-
APPLICATION SPEC	-	-
WEIGHT	-	-
CUSTOMER DRAWING		

Tyco Electronics		Tyco Electronics Corporation Harrisburg, PA 17105-3608	
NAME		VERTICAL HEADER, 3.81mm	
SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	00779	C-1776553	-
SCALE		SHEET	REV
3:1		1 OF 1	A2

8	1776553-8
POSN	PART NUMBER