



**Features :**

- 06 • For indoor use only, environmentally controlled areas. The enclosure can be used in air-handling spaces.
- 06 • cUL Listed to UL1863, also meets requirements of UL2043
- Fits into a 24"W x 24"L x 12"D raised floor opening. Suitable for a 2'x2' floor tile with U-shaped stringers.
- Box interior space = 20.9"Wx20.9"Lx7.9"D
- 2 openings sized to accept 16 RapidNet cassettes each. (1.20" max diameter cable per cassette)
- 06 • Firestop foam sealing kit to seal the 2 openings.
- 2 Firestop foam covers provided, accessible from inside of box.
- Inside mounting brackets for 19" EIA rack mounting. Universal vertical bracket hole spacing of 5/8"-5/8"-1/2" Threaded for #12-24 mounting screws.
- #12-24 panel mounting screws sold separately.
- Capable of 4RMU, vertical, fixed at center or 4" offset from Center.
- Provision for 4 cable tie brackets for securing routed wire cables.
- Provided with 4 T50L plenum rated cable ties for use with the cable tie brackets.
- Load capacity = 85 pounds of equipment total.
- Provided with 4 raised floor Support brackets.
- Provided with 4 1/4"-20 hex head box leveling screws.
- Provided with 2 grounding screws to outside of box.
- No cover provided, standard 2'x2' floor tile to cover top.
- Floor tile seal provided on top flange of box.
- RoHS compliant.

**HellermannTyton.**

ALL PROPRIETARY RIGHTS IN THE SUBJECT MATTER SHOWN ON THIS DRAWING ARE EXCLUSIVE PROPERTY OF HELLERMANN TYTON

name	date	city	state

NOTES

REVISIONS	DR level	06
	AW by	KAC
	date	01/13/2009
	ECN #	011211
	part level	-

DIMENSIONS	.XXXX = ±.0005
	.XXX = ±.005
	.XX = ±.01
	.X = ±.03
	∠ = ±0.5°
unless otherwise specified	
units	inches

PART	number	HTZB2X2	phase	Production
	name	2'X2' ZONE BOX ASSEMBLY		
	material	ALUMINUM .06 THK		

DRAWING	format	D	SW 2007	scale	1:2.5
	version	N	CAD		
	computer file number	M107-012-001CST_06	previous number		
	drawn	KAC	KAC		
	date	06/06/2008	checked	01/13/2009	approved
type	Customer			sheet 1 of 1	
number	M107-012-001CST				