



NOTES:

- METALHELLS: STEEL; min. 315µin TIN over 40-80µin NICKEL
- INSULATORS: PBT GF UL 94 V-0, GREEN
- SIGNAL CONTACTS: COPPER ALLOY
PLATING: GOLD FLASH over NICKEL
- NO CONTACTS ON POS. A1 - A4
- CONNECTOR IS PART MARKED: 3009W4SAR99A10X CONEC ABC

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND					tolerance	dim. in mm	scale:	2:1 (5:1)		
					date		name	material:	SEE NOTES	
					drawn	11.05.11	Heneboel	title: D-SUB COMBINATION FEMALE (b) 9W4S		
					appd.	11.05.11	Koch			
					norm			dwg no:	Inventor 10	DIN-A3
				d-old					sh: 1	
1 x b	A3999	12.05.2011	K.H.			part no:		3009W4SAR99A10X		
a	Original									