



Wire _____ Tinned copper
 Gauge _____ AWG 28/7 0,089 mm²
 Voltage rating _____ 300 Vr.m.s
 Current rating _____ 2,1A at 25°C
 Capacity unbalanced _____ 45,9 pF/m at 1 MHz
 Impedance unbalanced _____ 105 Ω
 Propagation delay _____ 4,9 ns/m nominal
 Insulation material _____ PVC
 Temperature rating _____ -20°C (operating) to +105°C
 _____ -30°C (static)
 Flammability rating _____ Flame retardant VW1
 Insulation resistance _____ 100 MΩ/km
 Approval _____ UL AWM style 2651

A					Det.	Name	 All Dim. in mm Orig. Size DIN A 4	SEK 18 flat cable 37 poles	Maßstab/ Scale
				Detail.	20/10/05	JMDR			10:1
				Insp.					
				Stand.					
			EC01360	19/02/10	SC	HARTING EURL F-95972 Paris		TB 09 18 037 700X	Blatt/ Page
			34400	18/09/07	PK				1
			33246	20/10/05	JMDR				1
			Mod.	Det.	Name			Sub.	
09 18 037 7004		100 m (328 feet)							
09 18 037 7001		30,48 m (100 feet)							
Part number		Length per reel							