



- NOTES:**
- METALSHELLS: STEEL; min. 320µ" TIN
 - INSULATORS: PBT GF UL 94 V-0, GREEN
 - SIGNAL CONTACTS: COPPER ALLOY
PLATING: min. 30µ" HARD GOLD OVER min. 50µ" NICKEL
SOLDER CUP ACCEPTS CABLE AWG 20
 - NO CONTACTS ON POS. A1 - A7
 - THREADED INSERT: COPPER ALLOY; min. 200µ" TIN over 80µ" NICKEL
 - COLLAR: COPPER ALLOY; min. 200µ" TIN over 80µ" NICKEL
 - MAXIMUM TORQUE VALUE FOR THREAD: 6" LBS
 - CONNECTOR IS PART MARKED: 3024W7SCM99A30X CONEC Y/W/W
 - [] = CRITICAL DIMENSION

Directive 2002/95/EC
"RoHS"
Compliant

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	
CUSTOMER APPROVAL DATE:	
NAME:	TITLE:
COMPANY NAME:	
APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY, WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND			
rev.	description	date	name

tolerance		scale:	2:1 (5:1)
	dim. in mm	material:	SEE NOTES
2003	date	title:	
drawn	04.03.	D-SUB COMBINATION FEMALE 24W7S SOLDER CUP with threaded insert	
appd.	04.03.		
norm			
d-old			
		dwg no:	AutoCAD 2000
CONEC		13K1A803	
		part no: 3024W7SCM99A30X	
		DIN-A	3
		sh: 1/1	