



ニッケル (2 μm MIN.) 下地 金 (0.35 μm MIN.) GOLD (0.35 μm MIN.) OVER NICKEL (2 μm MIN.)	無 NO	39-00-0295	1189AGL	バラ端子 LOOSE
		39-00-0293	1189AG	連鎖状端子 CHAIN
銅 (0.5 μm MIN.) 下地 錫 (0.9 μm MIN.) TIN (0.9 μm MIN.) OVER COPPER (0.5 μm MIN.)	有 YES	39-00-0294	1189GL	バラ端子 LOOSE
	無 NO	39-00-0289	1189ATL	バラ端子 LOOSE
メッキ PLATING	有 YES	39-00-0288	1189TL	バラ端子 LOOSE
	無 NO	39-00-0281	1189AT	連鎖状端子 CHAIN
	有 YES	39-00-0282	1189T	連鎖状端子 CHAIN
	デンプル有無 WITH DIMPLE	EDP.NO.	ENG.NO.	形状 FORM

注記 NOTES:
1. 一般公差 : ±0.4
GENERAL TOLERANCES: ±0.4

材料 MATERIAL	黄銅 BRASS	0.264t
適用電線範囲 WIRE RANGE	AWG# 14-#20	
被覆外径 INS. RANGE	∅ 1.6~4.1	

REVISED EC NO: J2010-2186 DRW:RTS/UR/OKA 2010/05/17 CHK'D:THARUYAMA 2010/05/17 APPR:HHIRATA 2010/05/21	DESCRIPTION	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY	SCALE 5:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION	
		10 UNDER	± ---	DRAWN BY HHASEGAWA	DATE 1993/07/06	TITLE .093 DIA.FEMALE TERM.		
		10 OVER 30 UNDER	± ---	CHECKED BY HHIRAMOTO	DATE 1993/07/06	MOLEX INCORPORATED		
		30 OVER	± ---	APPROVED BY MFUKUSHIMA	DATE 1993/07/06	DOCUMENT NO. SD-1189-002	SHEET NO. 1 OF 1	
J	REV	ANGULAR	± --- °	SEE TABLE		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS						