



**Material:**

- 1.Cable: #28,UL2919, 3COAXIAL+7C+1+AL/MY+Braid, (Beige PVC Jacket) O.D:8.5
- 2.Connectors: HD15M,9th Empty, Black
- 3.Thumbscrew:#4-40UNC, E32
- 4.Ferrite Core Size:RH16\*28\*9
- 5.Black Heat Shrink∅1.5x15:6PCS ∅3x8:6PCS
- 6.Copper Tape:30X50

**Note:**

- 1.Total Length:10000±50mm
- 2.Color: Beige
- 3.Molded Type

**Configuration:**

HD15M		HD15M	
1	Red(Coax)	1	
6	Red(Ground)	6	
2	Green(Coax)	2	
7	Green(Ground)	7	
3	Blue(Coax)	3	
8	Blue(Ground)	8	
4	Brown	4	
5	Black	5	
13	Green	13	
14	Red	14	
10	Orange	10	
11	White	11	
12	Yellow	12	
Shield	(Braid)	Shield	

Description	
Name	AK3780XF-R
HD15 Male-HD15 Male W/Copper Foil+2Ferrite Core	



THIS DRAWING IS UNPUBLISHED  
 © Copyright 2005 by Assmann Electronic Components All International Rights Reserved  
 This drawing is a controlled document for Assmann Electronics, Inc. It is subject to change and the controlling engineering organization should be contacted for the latest revision.

1

2

3

4