

## UFBK-BE


### Discontinued item

Order No.: 2783095

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2783095>

Base element with inductive decoupling for protective plug UFBK and UFBK-M, with universal foot for mounting on NS 32 or NS 35/7.5, housing width: 17.5 mm

#### Commercial data

GTIN (EAN)	 4 017918 069810
Note	Made-to-order
sales group	J223
Pack	10 pcs.
Customs tariff	85363010

#### Product notes

WEEE/RoHS-compliant since:  
02/14/2006



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

#### Technical data

##### General

Conductor cross section stranded min.	0.2 mm <sup>2</sup>
Conductor cross section stranded max.	2.5 mm <sup>2</sup>
Conductor cross section solid min.	0.2 mm <sup>2</sup>
Conductor cross section solid max.	4 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12

Nominal current I <sub>N</sub>	2 A
Ambient temperature (operation)	-40 °C ... 80 °C
Inflammability class acc. to UL 94	V2
Degree of protection	IP20
Pitch unit	1 Div.

### Certificates / Approvals



Certification

GOST

### Accessories

Item	Designation	Description
<b>Plug/Adapter</b>		
2781576	CS-UFBK	Keying pins for later keying of the base elements without keying belonging to the PLUGTRAB UFBK and UAK product ranges.

**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact  
Technical modifications reserved;