

SL20 with 48...56V

SL20.113

- Input: AC 115/230V **auto select**
- Output: 48...56V / 480W
- 93% Efficiency
- Ideal for parallel operation

PULS

CB
scheme
IEC60950

c UL US

UL508 LISTED
IND. CONT. EQ.
18 WM, 60°C

UL US
UL60950 E137006
CUL/CSA-C22.2
No 60950

Type approval
acc. to:

- IEC / EN60950
- EN50178
- Overvolt. cat. III
- EN60204

CE
EMC and
Low Volt.
Directive



Data sheet

Datasheet

Input

Input voltage	AC 100-120V/220-240V, 47-63Hz, auto select
Rated tolerances	
• Continuous	AC 85...132V or AC 184...264V
• Short-term (30s) at 48V/10A	AC 85...140V or AC 175...280V
Input current I_n	<12A (115V range) <6A (230V range)
Inrush current limiting with active bypass of the limiting resistor (NTC).	
Inrush current I_{pk}	<18A @ AC 264V ($T_{amb} = +25^\circ\text{C}$, cold start) <37A @ AC 264V ($T_{amb} = +50^\circ\text{C}$, cold start)
Fuse loading I^2t	<5A ² s ($T_{amb} = +25^\circ\text{C}$, cold start) <8A ² s ($T_{amb} = +50^\circ\text{C}$, cold start)
To be fused with a 16A, B-type 'circuit-breaker' switch based on the usual thermomagnetic overload sensing principle (used anyway to fuse the input lines).	
Transient handling	Transient resistance acc. to VDE 0160 / W2 (750V / 1.3ms), for <i>all</i> load conditions.
Hold-up time	30ms at 48V/10A, AC 230V _{in} 35ms at 48V/10A, AC 120V _{in} 15ms at 48V/10A, AC 100V _{in}

Efficiency, Reliability etc.*

Efficiency	typ. 93% (AC 230V, 48V/10A)
Losses	typ. 36.2W (AC 230V, 48V/10A)
MTBF	519.000h acc. to Siemensnorm SN29500 (48V/10A, 230V, $T_{amb} = 40^\circ\text{C}$)
Life cycle (electrolytics)	The unit exclusively uses longlife electrolytics, specified for +105°C (cf. 'The SilverLine', p.2). High reliability, as <ul style="list-style-type: none"> • only five aluminium electrolytics and • no small aluminium electrolytics are used.

* For further information see data sheets „The SilverLine“, „SilverLine Family Branches“ and mechanics data sheet SL20

Order information

Order number	Description
SL20.113	
SLZ02	(wall mounting set; contains 2 pcs.)

Output

Output voltage	DC 48...56V, adjustable by (covered) front panel potentiometer; preset: 48V $\pm 0.5\%$ Adjustment range guaranteed
Output noise suppression	Radiated EMI values below EN50081-1, even when using long, unshielded output cables.
Ambient temperature range T_{amb}	Operation: $0^\circ\text{C} \dots +70^\circ\text{C}$ (> 60°C : Derating) Storage: $-25^\circ\text{C} \dots +85^\circ\text{C}$
Rated continuous loading with convection cooling:	
• $T_{amb} = 0^\circ\text{C} - 60^\circ\text{C}$ short-term (<30s)	48V/10A resp. 56V/8.6A 48V/12.5A resp. 56V/10.7A
Derating	12W/K (at $T_{amb} = 60-70^\circ\text{C}$)
Voltage regulation	better 2% over all
Ripple	incl. spikes (20MHz bandw.), 50Ω measurem.
• Output charact. S	<40mV _{pp} (<0.09%)
• Output charact. P	<80mV _{pp} (In: AC 230V, Out: 48V/10A)
(S/P: Single/Parallel Mode)	<100mV _{pp} (In: AC 184V, Out: 56V/8.6A)
Over-voltage protection	At 58.6V $\pm 2.3\%$: switch to hiccup mode
Front panel indicators:	
• Green LED on, when $V_{out} = V_{out}$ adjusted	
• Red LED on, when $V_{out} < V_{out}$ adjusted	
Parallel operation	Yes, up to ten SL20

To achieve current sharing the output V/I characteristic can be altered to be 'softer' (47.9V at 0A, 45.6V at 10A). This is done by repositioning an external bridge connection (without opening the unit).

Power Back Immunity max. 57V

Construction/ Mechanics*

Housing dimensions and Weight	
• W x H x D	220mm x 124mm x 102mm (+ DIN rail)
• Free space for ventilation	above/below 70mm recommended left/right 25mm recommended
• Weight	1.8kg

Design advantages:

- All connection blocks are easy to reach as mounted on the front panel.
- PVC insulated cable can be used for all connections, as the connection blocks are mounted in the cooler area on the underside of the unit.

Start / Overload Behaviour

Start-up delay	typ. 0.55s
Rise time	appr. 20-80ms, depending on load
Overload behaviour	Puls Overload Design (see right-hand diagram)

Advantages:

- No disconnection/hiccup, thus overloading is possible also for a longer period of time (load start-up), ideal for parallel operation.
- High overload/short-circuit current due to straight characteristic; each bias point of the V/I characteristic extends 10A.
- Advantage: Due to the high and continuously supplied overload current the unit starts reliably even with awkward loads (DC-DC converters, motors). No 'sticking' can occur as, for example, with fold-back characteristics, and secondary fuses trigger more reliably.

Further information


Further information, especially about

- EMC
- Connections
- Safety, Approvals
- Mechanics and Mounting,


see page 2 of the „The SilverLine“ data sheet

For detailed dimensions
see SilverLine mechanics data sheet SL20



Output characteristic (typ.)



Efficiency (typ., at V_{out}=48V)



Hold-up time (min., at V_{out}=48V)



Unless otherwise stated, specifications are valid for AC 230V input voltage, +25°C ambient temperature, and 5 min. run-in time. They are subject to change without prior notice.

Your partner in power supply:



European Power Supply Manufacturers Association



Bayerns Best 50
Czech 100 Best
Europe's 500

PULS GmbH
Arabellastraße 15
D-81925 München
Tel.: +49 89 9278-0
Fax: +49 89 9278-199
www.puls-power.com