


RSM-Series RSM 8R 24VDC LP GEM.-

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com



Clip-on RS 30. 31. 32 relay bases are available in widths from 11.2 to 25 mm, depending on the type.

The RSM relay multiplexers are available as 4, 8 and 16-way modules. To reduce the wiring work, the DC variants are fitted with a common plus or minus potential. The optional IEC603-1 plug-in connector enables the connection of pre-assembled lines.

The screw connection system is used to connect the conductor with a rated cross-section of 2.5 mm².

General ordering data

Order No.	1107761001
Type	RSM 8R 24VDC LP GEM.-
Version	RSM-Series, Relays, No. of contacts: 1, CO contact, AgNi 90/10, Rated control voltage: 24 V DC, Continuous current: 6 A, Screw connection
GTIN (EAN)	4032248047727
Qty.	1 pc(s).

RSM-Series
RSM 8R 24VDC LP GEM.-

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data
Ratings

Conductor connection system	Screw connection	Humidity	40 °C / 93 % rel. humidity, no condensation
Wire cross-section, solid, max.	2.5 mm ²		

Dimensions and weights

Width	145 mm	Height	87 mm
Depth	76 mm	Net weight	317 g

Temperatures

Operating temperature	-25 °C...+50 °C	Storage temperature	-40 °C...+60 °C
-----------------------	-----------------	---------------------	-----------------

Connection data

Clamping range, rated connection	2.5 mm ²	Clamping range, rated connection, min.	0.5 mm ²
Clamping range, rated connection, max.	4 mm ²	Stripping length, rated connection	8 mm
Wire connection cross section, finely stranded, max.	2.5 mm ²		

Input

Rated control voltage	24 V DC	Rated current DC	6 A
Power rating	0.45 W	Pull-in / drop-out current, DC coil	12 mA / 2 mA
Status indicator	LED yellow		

Output

Max. switching voltage, AC making current	250 V	Continuous current	6 A
Switch-on delay	8 A	Max. switching power	2000 VA
Duration of Bounce	< 8 ms	Switch-off delay	< 7 ms
Max. switching frequency at rated load	≤ 3 ms	Min. switching power	250 mW
	0.1 Hz		

Contact specifications

No. of contacts	1	Contact design	CO contact
Contact material	AgNi 90/10	Mechanical service life	30 x 10 ⁶ switching cycles
Electrical service life of AC coil	> 7x10 ³ Switching cycles	Electrical service life, DC coil	> 5x10 ⁵ switching cycles

Insulation coordination

Rated voltage	250 V	Clearance and creepage distances for control side - load side	> 3 mm
Impulse withstand voltage	4 kV	Protection degree	IP 20
Pollution severity	2	Surge voltage category	III

Other technical data

Version	Relay coupler	Status indicator	LED yellow
Free-wheel diode	Yes	Reverse polarity protection	Available

**RSM-Series
RSM 8R 24VDC LP GEM.-**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Further details of approvals / standards

Standards DIN EN 50178

Classifications

ETIM 2.0	EC001437	ETIM 3.0	EC001437
UNSPSC	30-21-19-17	eClass 4.1	40-02-06-14
eClass 5.1	27-37-16-01	eClass 6.0	27-37-16-01
eClass 7.0	27-37-16-01		

Approvals

Approvals



Downloads

Declaration of Conformity [K34_05_10.pdf](#)