

## Plastic label with drill hole - EMLP 32 (38X14) BK - 0822327

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

Plastic label with drill hole, Card, black, Unlabeled, Can be labeled with: Engraving, Plotter, Mounting type: Adhesive, Lettering field: 38 x 14 mm



The figure shows the product version  
EMLP 32 (38X14) SR

### Product Features

- Can be engraved using the P1 ENGRAVING UNIT
- Can be labeled easily using the CMS-P1-PLOTTER
- High level of resistance to chemical and mechanical influences
- High-quality appearance
- Labeling service: Phoenix Contact can custom-label all EMLP ... markers according to your requirements
- For marking components, devices, and buttons

### Key commercial data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 pc     |
| Weight per Piece (excluding packing) | 24.7 GRM |
| Custom tariff number                 | 39203000 |
| Country of origin                    | Belgium  |

### Technical data

#### Dimensions

|            |       |
|------------|-------|
| Length (b) | 50 mm |
| Width (a)  | 38 mm |

#### Ambient conditions

|                                 |                                 |
|---------------------------------|---------------------------------|
| Ambient temperature (operation) | -40 °C ... 120 °C               |
| Recommended storage conditions  | 20 °C / 50 % relative humidity. |

#### General

|            |                                |
|------------|--------------------------------|
| Color      | black                          |
| Components | free from silicone and halogen |
| Material   | TRANSPLY-ABS                   |

## Plastic label with drill hole - EMLP 32 (38X14) BK - 0822327

### Technical data

#### General

|                                     |                             |
|-------------------------------------|-----------------------------|
| Wipe resistance                     | DIN EN 61010-1 (VDE 0411-1) |
| Number of individual labels         | 6                           |
| Number of individual labels per row | 2                           |
| Adhesive                            | Acrylic                     |
| Printability                        | Plotter                     |
| Device                              | 5144615 CMS-P1-PLOTTER      |
|                                     | 5145546 P1 ENGRAVING UNIT   |
| Adhesive strength                   | 50 µm                       |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 24190208 |
| eCl@ss 4.1 | 24190208 |
| eCl@ss 5.0 | 27149103 |
| eCl@ss 5.1 | 27141137 |
| eCl@ss 6.0 | 27141137 |
| eCl@ss 7.0 | 27141137 |
| eCl@ss 8.0 | 27141137 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000761 |
| ETIM 3.0 | EC000761 |
| ETIM 4.0 | EC000761 |
| ETIM 5.0 | EC000761 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121410 |
| UNSPSC 12.01  | 39121410 |
| UNSPSC 13.2   | 39121410 |