

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-25°C TO +85°C	STORAGE TEMPERATURE RANGE	-25°C TO +60°C
	OPERATING&STORAGE HUMIDTY RANGE	85 % MAX	APPLICABLE CABLE	CABLE DIAMETER : $\phi 8.8 \pm 0.5$

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
------	-------------	--------------	----	----

CONSTRUCTION

GENERAL EXAMINATION	TEST METHOD	REQUIREMENTS	QT	AT
	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X

COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE

REMARK	APPROVED	CHECKED	DATE
Unless otherwise specified, refer to JIS C 5402.	A0. SUZUKI		09. 10. 05
	KN. ICHIKAWA		09. 10. 02
	TU. TANIGUCHI		09. 10. 02
	DRAWN TU. TANIGUCHI		09. 10. 02

Note QT:Qualification Test AT:Assurance Test X:Applicable Test	DRAWING NO.	ELC4-126659-00
--	-------------	----------------

HRS	SPECIFICATION SHEET	PART NO.	DH-37-CMB (8. 8)	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL244-0033-0-00	1/