

| APPLICABLE STANDARD | | | | |
|---------------------|-----------------------------|--------------------------|---------------------------|---------------------------------|
| RATING | OPERATING TEMPERATURE RANGE | -35°C TO +85°C (NOTES 1) | STORAGE TEMPERATURE RANGE | -10°C TO +60°C (NOTE3) |
| | OPERATING HUMIDITY RANGE | 20 % TO 80 % (NOTES 2) | STORAGE HUMIDITY RANGE | 40 % TO 70 % (NOTE3) |
| | VOLTAGE | 150 V AC (DC) | CURRENT | 1 A |
| | APPLICABLE CONNECTOR | DF13-*S-1.25C | APPLICABLE CONTACT | DF13(G)-2630SCF DF13-3032SCF |

SPECIFICATIONS

| ITEM | TEST METHOD | REQUIREMENTS | QT | AT |
|------|-------------|--------------|----|----|
|------|-------------|--------------|----|----|

CONSTRUCTION

| | | | | |
|---------------------|---------------------------------------|-----------------------|---|---|
| GENERAL EXAMINATION | VISUALLY AND BY MEASURING INSTRUMENT. | ACCORDING TO DRAWING. | X | X |
| MARKING | CONFIRMED VISUALLY. | | X | X |

ELECTRIC CHARACTERISTICS

| | | | | |
|-----------------------|--------------------------|----------------------------|---|---|
| CONTACT RESISTANCE | 100 m A (DC OR 1000 Hz). | 30 mΩ MAX. | X | - |
| INSULATION RESISTANCE | 100 V DC. | 500 MΩ MIN. | X | - |
| VOLTAGE PROOF | 500 V AC FOR 1 min. | NO FLASHOVER OR BREAKDOWN. | X | - |

MECHANICAL CHARACTERISTICS

| | | | | |
|----------------------|--|--|---|---|
| MECHANICAL OPERATION | 30 TIMES INSERTIONS AND EXTRACTIONS. | ① CONTACT RESISTANCE: 30 mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS. | X | - |
| VIBRATION | FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, AT 2 h, FOR 3 DIRECTIONS. | ① NO ELECTRICAL DISCONTINUITY OF 1μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS. | X | - |
| SHOCK | 490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS. | | X | - |

ENVIRONMENTAL CHARACTERISTICS

| | | | | |
|------------------------------|--|--|---|---|
| RAPID CHANGE OF TEMPERATURE | TEMPERATURE -55→ 15 TO 35→+85→ 15 TO 35 °C TIME 30→ 2 TO 3→30→ 2 TO 3 min. UNDER 5 CYCLES. | ① CONTACT RESISTANCE: 30mΩ MAX. ② INSULATION RESISTANCE: 500 MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS. | X | - |
| DAMP HEAT (STEADY STATE) | EXPOSED AT 40 ± 2 °C, 90 TO 95 %, 96 h. | | X | - |
| RESISTANCE TO SOLDERING HEAT | 1) FLOW SOLDERING 250°C, FOR 10 sec. 2) MANUAL SOLDERING SOLDERING IRON TEMPERATURE :300°C, SOLDERING TIME : 3sec. NO STRENGTH ON CONTACT. | NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS. | X | - |
| SOLDERABILITY | SOLDERED AT SOLDER TEMPERATURE, 240°C FOR INSERTION DURATION, 3sec. | SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMersed. | X | - |

REMARKS

NOTE1: INCLUDE THE TEMPERATURE RISING BY CURRENT

NOTE2:NO CONDENSING

NOTE3:APPLY TO THE CONDITION OF LONG TERM STORAGE FOR UNUSED PRODUCTS BEFORE PCB ON BOARD,

AFTER PCB BOARD , OPERATING TEMPERATURE AND HUMIDITY RANGE IS APPLIED FOR INTERIM STORAGE DURING TRANSPORTATION.

Unless otherwise specified, refer to JIS C 5402.

| COUNT | DESCRIPTION OF REVISIONS | DESIGNED | CHECKED | DATE |
|-------|--------------------------|----------|---------|------|
| △ | | | | |

| | | | |
|--|----------|---------------|----------|
| | APPROVED | TS. SAKATA | 09.12.07 |
| | CHECKED | TS. FUKUSHIMA | 09.12.07 |
| | DESIGNED | KT. ISHII | 09.12.05 |
| | DRAWN | KT. ISHII | 09.12.05 |

Note QT:Qualification Test AT:Assurance Test X:Applicable Test DRAWING NO. ELC4-083673-08

| | | | | |
|------------|---------------------------|----------|-----------------------|-------|
| HRS | SPECIFICATION SHEET | PART NO. | DF13-*P-1. 25DSA (20) | |
| | HIROSE ELECTRIC CO., LTD. | CODE NO. | CL536 | △ 1/1 |