

126-00099

Article Number: 126-00099



HellermannTyton



Download drawing



Download spec sheet

Base Data

Local Order Number 126-00099

Type T50SOSKSFT5SE

Color Black (BK)

Features and Benefits When inserted into the hole the arrowhead locks into place and the 'disc', between the fixing and the head of the cable tie, covers the hole and minimises the ingress of dust, dirt and water. The anchor will adjust for variations in panel thickness thereby ensuring a secure fixing at all times.
The T50SST type has a small 'tab' placed below the head, which gives additional protection against axial forces and is particularly useful to assist retention on convoluted tubing.

Fixation Method (FF) Arrowhead

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Outside Serrated

Product Dimensions

Minimum Tensile Strength (Imperial) 40.0 lbs

Minimum Tensile Strength (Metric) 180 N

Length L (Imperial) 6.2 "

Length L (Metric) 156.0 mm

Width W (Imperial) 0.18 "

Width W (Metric) 4.6 mm

Bundle Diameter Min. (Imperial) 0.04 "

Bundle Diameter Min. (Metric) 1.0 mm

Bundle Diameter Max. (Imperial) 1.38 "

Bundle Diameter Max. (Metric) 35.0 mm

Disc Diameter (Imperial) 0.63 "

Disc Diameter (Metric) 16.0 mm

Panel Thickness Max. (Imperial) 0.051 "

Panel Thickness Min. (Imperial) 0.027 "

Mounting Hole Diameter D (Imperial) 0.189-0.205 "

Mounting Hole Diameter D (Metric) 4.8 - 5.2 mm

Mounting Hole Diameter D Min. (Imperial) 0.189 "

Mounting Hole Diameter D Max. (Imperial) 0.205 "

Thickness T (Imperial) 0.05 "

Mounting Hole Diameter D Max. (Metric) 5.2 mm
Mounting Hole Diameter D Min. (Metric) 4.8 mm
Thickness T (Metric) 1.3 mm

Logistics and Packaging

Quantity Per bag
Package Quantity (Metric) 1000 Pieces
Carton Quantity 6000 Pieces
Weight (Metric) 1.5 kg

Material and Specifications

Material Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut PA66HS
Flammability UL94 V2
Minimum Extraction Force (Imperial) 40.0 lbs
Minimum Extraction Force (Metric) 180 N
Operating Temperature -40°F to +221°F (-40°C to +105°C)
ROHS compliant (Article 4 - 1) Yes