



NOTE

1. 嵌合相手：503763シリーズ
MATES WITH：503763 SERIES
2. 適合ターミナル：503765シリーズ
APPLICABLE TERMINAL：503765 SERIES
偶数極に適用
APPLY EVEN CIRCUIT PRODUCTS
4. 材料
MATERIAL
耐熱性樹脂 UL94-V0 BLACK
HEATPROOF RESIN UL94-V0 BLACK
5. ELV及びRoHS適合品
ELV AND ROHS COMPLIANT
6. コネクタの取扱いについては、AS-503764-001/002を参照
PLEASE REFER TO AS-503764-001/002

6.6	7	8.6	3.0	5037640401	4
4.6	5	6.6	1.0	5037640201	2
D	C	B	A	ORDER No.	CIRCUIT

RELEASED EC NO: J2014-1278 DRWN: YWAKE 2014/03/03 CHKD: KASAKAWA 2014/03/03 APPR: NUKITA 2014/03/05	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE	SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION
			MM ONLY	10:1	METRIC	
	DESCRIPTION	10 UNDER	±0.2	DRAWN BY	DATE	TITLE
	REV	10 OVER 30 UNDER	±0.25	YWAKE	2014/03/03	1.0 WIRE TO BOARD CONN. R/A H=1.5MM REC CRIMP HOUSING molex SD-503764-001
	30 OVER	±0.3	CHECKED BY	DATE		
	ANGULAR	±3 °	KASAKAWA	2014/03/03		
	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		APPROVED BY	DATE		
			NUKITA	2014/03/05		
			MATERIAL NO.	DOCUMENT NO.	SHEET NO.	
			SEE CHART		1 OF 1	
			SIZE	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		
			A3			