

## Specification Sheet

Part Number: RTT750HR.NX900



Releasable Cable Tie, 29.6" Long, 200 lb Tensile Strength, PA66, Yellow, 5/pkg

<b>Article Number</b>	115-00001
<b>Type</b>	SpeedyTie (RTT750HR)
<b>Color</b>	Red (RD) Yellow (YE)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• The heavy duty Speedy tie features a specially designed head and patented trigger to allow for repeated use in temporary bundling applications. • Additional design feature on the head allows excess strap to be tucked away after installation.</li></ul>
<b>Quantity Per</b>	bag
<b>Product Description</b>	HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes or temporary bundling are necessary. The head design guarantees high tensile strength even after repeated use.
<b>Short Description</b>	Releasable Cable Tie, 29.6" Long, 200 lb Tensile Strength, PA66, Yellow, 5/pkg

Global Part Name

SpeedyTie (RTT750HR)-PA66-RD/YE

Minimum Tensile Strength (Imperial)

200.0

Minimum Tensile Strength (Metric)

888.0

Length L (Imperial)

29.6

Length L (Metric)

752.0

Identification Plate Position

none

Releasable Closure

Yes

Tie Closure

plastic pawl

Variant

Inside Serrated

Width W (Imperial)

0.51

Width W (Metric)

13.0

Bundle Diameter Min (Imperial)

1.6

Bundle Diameter Min (Metric)

40.0

Bundle Diameter Max (Imperial)

8.3

Bundle Diameter Max (Metric)

210.0

Thickness T (Imperial)

0.075

Thickness T (Metric)

1.9

<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL 94 V2
<b>Operating Temperature (Metric)</b>	-40°F to +185°F (-40°C to +85°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	5
<b>Package Quantity (Metric)</b>	5
<b>Customs Number</b>	3926909987
<b>Content Unit(BMEcat)</b>	pcs.
<b>Weight (Metric)</b>	23.2