



NOTES:

1. RoHS COMPLIANT
- (b) 2. METALSHELLS: STEEL; min. 315µin TIN over 40-80µin NICKEL
3. INSULATOR: HIGH TEMPERATURE PLASTIC UL 94 V-0, BLACK
- (c) 4. CONTACTS: COPPER ALLOY; PLATING (SEE PART NO.):
 - PLEASE ADD A for GOLD FLASH over NICKEL (PREFERRED TYPE)
 - PLEASE ADD B for 20µin HARD GOLD over min. 50µin NICKEL
 - PLEASE ADD C for 30µin HARD GOLD over min. 50µin NICKEL
5. SEALING COMPOUND: PUR; BLUE
6. CAPACITANCE: 180pF ± 20%
7. DIELECTRIC WITHSTANDING VOLTAGE: 424 VDC
8. CONNECTOR IS PART MARKED: 241□26860X CONEC ABC

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND			tolerance		scale: 2:1 (5:1)	
			date	name	material: SEE NOTES	
			drawn	30.06.09	Petker	title: D-SUB FILTER MALE 25pos. SOLDER CUP
			appd.	01.07.09	Fischer	
		norm			dwg no:	
3 x c		Ä4494	09.10.2012	K.H.	d-old	DIN-A3
1 x b		Ä 3387	15.07.2009	Petker	24K1A1183	
a		Origin			sh: 1	
rev.		description	date	name	part no: (c) 241□26860X (see note 3)	

CONEC®